


Pro-Jet™ Yellow OAM Liquid

▶ **A bright yellow dye-based liquid for a wide range of aqueous inkjet applications**

- ▶ Strong hue on a range of papers
- ▶ Highly purified to ensure low salt and metal content
- ▶ Good compatibility with a range of ink formulants
- ▶ Internationally registered



Typical Properties	
Chemical Class	Pyrazolone based dye
Strength	Liquid product contains nominally 7.5% active colorant
Typical loading in ink vehicle	60% w/w
pH Stability Range	7.0 - 9.0



Spectral Properties (in solution)	
Solution OD:	1.00 - 1.10 (@ 270 ppm)
λ max:	ca 426 nm
Physical Analysis	
Filterability:	Passes 0.45 micron
Viscosity at 25°C:	1.1 - 1.7 cps
Surface Tension at 25°C:	>/ = 45 dynes cm ⁻¹
Chemical Analysis	
Metals	Fe < 5 ppm
	Ca < 10 ppm
Salts	Cl < 150 ppm
	SO ₄ < 150 ppm

Related Dye-Based Liquids

Other Pro-Jet products in this range

- ▶ Pro-Jet™ Red OAM

Other Pro-Jet Magenta Yellow products

- ▶ Pro-Jet™ Yellow 1
- ▶ Pro-Jet™ Yellow 1G
- ▶ Pro-Jet™ Yellow 746
- ▶ Pro-Jet™ Yellow 492
- ▶ Pro-Jet™ Fast Yellow 2

Print Properties	Plain Paper	Photo Paper (Swellable)	Photo Paper (Microporous)
ROD	1.11	1.57	1.62
L*	87	89	91
a*	-4	-7	-6
b*	85	106	110
C	85	106	110
Hue	93	94	93
Light fastness (delta E)	n/a	60	49

Wet Fastness (Plain Paper)

Rated 6/10 on arbitrary scale where 1 = severe bleed and 10 = no bleed.

Prints prepared using a generic ink formulation containing 3.5% dye and having an ink pH of 8-9.

Spectral measurements carried out with Gretag Macbeth Spectrolino with D65 illumination and 2 degree observer.

Fade carried out using an Atlas Ci5000 Weatherometer for 100 hours at 70% density.

Product Registration

PRO-JET Yellow OAM Liquid is notified under the applicable toxic/regulatory statutes in EU, USA, Canada, Australia, Japan, Korea, China, Switzerland and the Philippines. Please check full product registration with your local FFIC sales manager.

Product Packaging

This product is available in 20kg and 200kg packages as standard and must be kept frost-free.

Product Safety

Please refer to the product MSDS which is available in most major European languages, in both EU and US format.

For further information on Pro-Jet™ dye-based liquids please contact:

EUROPE

FUJIFILM Imaging Colorants Ltd.
Earls Road
Grangemouth
Stirlingshire
FK3 8XG
Scotland

Tel: +44 (0) 1324 468468
Fax: +44 (0) 1324 483537

USA

FUJIFILM Imaging Colorants Inc
233 Cherry Lane
New Castle
DE 19720
USA

Tel: +1 800 552 1609
Fax: +1 302 477 8025

JAPAN

Fine Chemicals Business Group
Industrial Products Division
FUJIFILM Corporation
7-3, Akasaka 9-Chome, Minato-ku,
Tokyo 107-0052
Japan

Tel: +81 3 6271 3040
Fax: +81 3 6271 3164

e projet@fujifilmic.com

www.fujifilmimagingcolorants.com

The information contained in this publication is based upon in-house testing by FUJIFILM Imaging Colorants and is accurate to the best of our knowledge, information and belief at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine applicability of such information or the suitability of any products for their own particular purpose and their freedom to operate with respect to patents.

Supply of this product is subject to FFIC's standard terms and conditions.

Pro-Jet™ is a trademark of FUJIFILM Imaging Colorants Limited.
The FUJIFILM name and logo are trademarks owned by FUJIFILM Corporation.

September 2011

innovatingenablingcoloring